

GeForce GTX 280 *HYDRO COPPER 16*

Part Number: 01G-P3-1289-AR

- 1GB DDR3 Memory
- DirectX 10 Support
- 2nd Generation Unified Architecture
- PCI-E 2.0 Support



At A Glance

- GeForce GTX 280 (691MHz clock)
- 1GB 512-bit 0.8ns GDDR3 Memory (1215MHz clock - 2430MHz effective)
- 1458MHz Shader Clock
- 240 Processing Cores
- PCI Express 2.0
- Dual DVI-I Connectors
- 155.52GB per second memory bandwidth



PRECISION
EVGA ADVANCED GRAPHICS TUNING



24/7*
Tech Support
888 · 881 · EVGA
www.evga.com/24-7
*24/7 North America only

Features

- 2nd Generation NVIDIA® Unified Architecture
- Full Microsoft® DirectX® 10
- NVIDIA 2-way and 3-way SLI Ready
- NVIDIA® PureVideo™ HD technology
- NVIDIA® PhysX Ready
- NVIDIA® CUDA technology
- NVIDIA® PureVideo™ HD technology
- PCI Express® 2.0 support
- Two dual-link DVI, and one HDTV
- Dual-link HDCP Capable
- OpenGL 2.1 Support

Interface
- HDTV
- DVI-I
- DVI-I

Dimensions

- height: 4.376in - 111.15mm
- length: 10.5in - 266.7mm



MODS RIGS™

YOUR GAMES, IN LIVING COLOR



THEY - NEXT GEN MYSTERY FPS BANG CAPTURED ON NVIDIA GPU. PROVIDED BY METROPOLIS SOFTWARE SP. Z. O. O

BEYOND GAMING



POLENS. © 2008 COOLPIX, INC.

