



e-GeForce4 MX 440-8X 64MB 32 bit DDR AGP 064-A8-NV65-LX



AT A GLANCE

- 256-bit GeForce4 MX 440-8X (250MHz clock)
- 64MB 32-bit 5ns 16x16 DDR Memory (166MHz clock - 266MHz effective)
- AGP 8X/4X Compatibility (AGP 3.0 Compliant)
- PC 99 DB-15 analog connector (VESA DDC2B + DPMS)
- Integrated NVIDIA TV Encoder (S-Video)
- 34 million Triangles / Sec. (chipset spec)
- 1.1 Billion Texels / Sec. (chipset spec)
- 1.06 GB per Second Memory Bandwidth

3D FEATURES

- NVIDIA Accuvision™ Antialiasing - includes FSAA (2X, 4X, 4XS, and Quincunx)
- Integrated Hardware Transform and Lighting engine (T&L)
- NVIDIA Shading Rasterizer™
- True Reflective Bump Mapping
- Cube Environment Mapping
- 32-bit Color with 32-Bit Z/Stencil Buffer
- DirectX® and S3TC® texture compression
- High Performance 2D Rendering engine
- Multi-Buffering (Double, Triple, Quad)
- 2 dual-rendering pipelines
- 4 texels per clock cycle

RESOLUTION CHART

	8-Bit	16-Bit	32-Bit
640 x 480	240Hz	240Hz	240Hz
800 x 600	240Hz	240Hz	240Hz
1024 x 768	240Hz	240Hz	200Hz
1152 x 864	200Hz	200Hz	170Hz
1280 x 960	170Hz	170Hz	150Hz
1280 x 1024	170Hz	170Hz	150Hz
1600 x 1024	120Hz	120Hz	100Hz
1600 x 1200	120Hz	120Hz	100Hz
1920 x 1080	100Hz	100Hz	85Hz
1920 x 1200	100Hz	100Hz	85Hz
1920 x 1440	85Hz	85Hz	75Hz
2048 x 1536	75Hz	75Hz	60Hz

Refresh rates shown are the highest obtainable and are monitor dependent. Resolutions, pixel depths and refresh rates are driver dependent and may not be available in all applications or operating system.



OTHER FEATURES

- Lightspeed Memory Architecture™ II
- NVIDIA nView™ multi-display technology
- NVIDIA Video Processing Engine (VPE)
- Integrated TV Encoder 10-Bit DAC
- Video Acceleration (DirectShow, MPEG-1, MPEG-2, Indeo, MS Bob and Weave)
- High-quality HDTV/DVD playback
- Integrated Dual 350MHz RAMDACs
- Integrated Dual-Channel TMDS Transmitters
- MPEG-2 Motion Compensation
- Integrated video field support (5-tap horizontal, 3-tap vertical)
- NVIDIA Digital Vibrance Control™ (DVC)

DRIVER SUPPORT

- AutoInstaller with ADM* Technology
- ResChanger©
- NVIDIA Unified Driver Architecture (UDA) (Windows 98/ME/NT 4.0/2000/XP)
 - Direct Draw
 - Direct3D
 - DirectVideo
 - DirectX
- Full OpenGL ICD for All Supported Operating Systems

DIMENSIONS

- height: 4.12in - 105mm
- length: 6.60in - 168mm

e-GeForce4 MX 440-8X 64MB 32 bit DDR AGP

www.evga.com - The Definitive VGA Online Community

Product Specs

2900 Saturn Street, Suite B Brea, CA 92821
Phone: (888) 881-eVGA Fax: (714) 528-4501

061504